

TECHNICAL SPECIFICATIONS

6750 Box Drill	5,7 mts			6,5 mts		
Number of openers	30 -32			34 - 36		
Row spacing	19,1 - 17,5 cm			19,1 - 17,5 cm		
Chassis type						
	Rigid, 2 fixed rear wheels and 2 front wheels movable over pivot shaft, floating hitch. Optional: 2-point hitch					
Single disc openers						
Disc diameter	46 cm					
Disc angle	7°					
Gauge wheels	Standard: 11,4 x 41 cm semi-pneumatic. Optional: 11,4 x 41 cm semi-pneumatic ribbed.					
Press wheels	semi-pneumatic 2,54 x 25,4cm					
Cover wheels	Standard: 2,54 x 30,4 cm nodular cast and 20° vertical. Optional: 35,58 cm star disc or double closing wheels with star discs.					
Openers hydraulics	Active hydraulic down pressure of up to 204 Kg per opener.					
Meters						
Grain	Sheave with 2 face socket					
Fertiliser	Chevron type forced feeding roller					
Pasture	Ribbed rotor of variable shift					
Gearbox						
Grain	Gearbox of 27 gears					
Fertiliser	Gearbox of 25 gears					
Pasture	Optional: gearbox of 25 gears					
Hopper capacities						
Pos. 1 (by default)	Grain: 250 lts/mts			Fertiliser: 220 lts/mts		
Pos. 2	Grain: 417 lts/mts			Fertiliser: 0 lts/mts		
Pos. 3	Grain: 187 lts/mts			Fertiliser: 283 lts/mts		
Pasture hopper	37,6 lts/mts					
General dimensions						
Distance between trees	1230 mm					
Ground clearance	250 mm					
Working width	4,5 mts	5,2 mts	6,1 mts	7,1 mts	8,3 mts	
Transport width	2,4 mts					
Height with folded drawbar	5,7 mts			6,5 mts		
Tyres	(4) 400/60 - 16,5					