

## TECHNICAL SPECIFICATIONS

### 12000 o 14000 Air Cart

<b>Tank Capacity</b>	<b>12000</b>	<b>14000</b>	<b>Fan</b>	<b>Meters</b>
Total capacity	12.830 lts	14.200 lts	Activation: hydraulic motor	Amount: 2 meter rolls
Front hopper	4.650 lts	5.080 lts	Size: 500 mm diametre	Roll segments: up to 8 segments divided by roll and 3 different measures
Rear hopper	8.180 lts	9.120 lts	Speed: 5,000 RPM	
Pressurised hoppers	SI	SI		
<b>Transmission</b>	<b>Standard:</b> mechanical boxes of variable rate <b>Optional:</b> electrohydraulic motors for variable seeding by prescription maps.			<b>Clutch:</b> Electromagnetic type
<b>General dimensions</b>	<b>Loading and unloading</b>			
Ground clearance: 57 cm.	<b>Standard:</b> hydraulically powered auger of 250 mm of diametre.			
Width: 3,9 mts.	<b>Optional:</b> hydraulically powered belt conveyor.			
Total length: 6,1 mts.	<b>Tyres: Standard:</b> AWT 23-1-26. <b>Optional:</b> AWT 23-1-30.			
Height: 3,5 mts.	<b>Tractor requirements:</b> closed centre hydraulic circuit; 2,250 psi.			
Weight: 3.800 Kg.	<b>Optionals:</b> hydraulic kit for activation with open centre tractors.			